

# ANTI FRICTION DRY PTFE LUBRICANT



## PRODUCT OVERVIEW

WD-40® Specialist® Anti Friction Dry PTFE Lubricant contains PTFE which provides enhanced lubrication, leaving a white dry film that won't attract dirt, dust or oil. It's quick drying and also great as a mould release agent. This product can be used on metals, plastic and glass.

## FEATURES AND BENEFITS

- ⊕ Dual action Smart Straw® applicator for wide area and precision spray applications
- ⊕ Ideal to be used on metals, plastic and glass
- ⊕ Enhanced lubrication and protection
- ⊕ Produces a white dry film that resists dirt, dust and oil
- ⊕ Reduces friction and wear
- ⊕ Advanced formulation works as an effective mould release agent
- ⊕ Excellent resistance to high temperature ranging from -45°C to +260°C

**NSF H2 Registered #145371**



NARROW SPRAY



WIDE SPRAY

## TYPICAL APPLICATIONS

Blades & Drill Bits, Power Tools & Equipment, Door & Window Tracks, Locks & Catches, Conveyors, Rollers, Chains & Cables, Hinges, Thermoplastics, Metal Extrusions.

## DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected. Dries in seconds.

## TECHNICAL DATA

PROPERTY	ANTI FRICTION DRY PTFE LUBRICANT
Appearance	Slightly cloudy, deep yellow liquid
Odour	Pleasant lemon odour
SG	0.71 - 0.74
Discharge rate	0.6 - 1.2 g/s
Temperature range	Effective performance at temperatures from -45°C to +260°C
Solubility	Not miscible with water
NSF category	H2
Flammability	Classed as extremely flammable under current legislation
Compatibility	Suitable for most surfaces, including plastic, metal and glass
Lubrication ASTM D-4172	Scar depth 0.43 mm
Extreme pressure lubrication ASTM 3233	2310 lb
Corrosion protection ASTM B-117	40% at 24h

## PACKAGING SPECIFICATIONS

PRODUCT NUMBER	UNIT SIZE	CASE SIZE
44394	400ml	400ml x 12

