



## Safety Data Sheet

### 1 - Identification

<b>Trade Name:</b> WD-40 Bike Dry Chain Lubricant	<b>Canadian Office:</b> WD-40 Products [Canada] Ltd. P.O. Box 220 Toronto, Ontario M9C 4V3 <b>Information Phone #:</b> (416) 622-9881 <b>Emergency Phone # 24 hr:</b> Canutec: (613) 996-6666 - Designated for use only in the event of chemical emergencies involving a spill, leak, fire exposure or accident involving chemicals
<b>Product Use:</b> Bike chain lubricant	
<b>Restrictions on Use:</b> None identified	
<b>SDS Date Of Preparation:</b> March 7, 2016	

### 2 – Hazards Identification

**WHMIS 2015/GHS Classification:**

Flammable Liquid Category 2

Aspiration Toxicity Category 1

Skin Irritant Category 2

Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

Note: This product is a consumer product and is labeled in accordance with the Consumer Chemicals and Containers Regulations (CCCR) which take precedence over WHMIS 2015 labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

**Label Elements:****DANGER!**

Highly flammable liquid and vapor.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Avoid breathing vapors or mists.

Wash thoroughly with soap and water after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

**Response**

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

In case of fire: Use water fog, dry chemical, carbon dioxide or foam to extinguish.

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**Disposal**

Dispose of contents and container in accordance with local and national regulations.

**3 - Composition/Information on Ingredients**

Ingredient	CAS #	Weight Percent	WHMIS 2015/ GHS Classification
Heptane	64742-49-0 142-82-5	30-50%	Aspiration Toxicity Category 1 Flammable Liquid Category 2 Skin Irritant Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (Nervous system effects)
Petroleum Base Oil	64742-53-6 64742-56-9 64742-65-0	<40%	Not Hazardous
Non-Hazardous Ingredients	Mixture	<30%	Not Hazardous
Cyclohexane	110-82-7	<5%	Aspiration Toxicity Category 1 Flammable Liquid Category 2 Skin Irritant Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

**4 – First Aid Measures**

**Ingestion (Swallowed):** Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

**Eye Contact:** Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. If irritation develops and persists, get medical attention.

**Inhalation (Breathing):** If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

**Signs and Symptoms of Exposure:** Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye, skin and respiratory tract irritation. Inhalation of vapors or mists may cause irritation, dizziness and drowsiness.

**Indication of Immediate Medical Attention/Special Treatment Needed:** Immediate medical attention is needed for ingestion.

**5 – Fire Fighting Measures**

**Suitable (and unsuitable) Extinguishing Media:** Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

**Specific Hazards Arising from the Chemical:** Highly flammable liquid and vapor. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Combustion will produce oxides of carbon, smoke fumes, unburned hydrocarbons. A vapor and air mixture can create an explosion hazard in confined spaces.

**Special Protective Equipment and Precautions for Fire-Fighters:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water.

**6 – Accidental Release Measures**

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

**Methods and Materials for Containment/Cleanup:** Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

## 7 – Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

**Conditions for Safe Storage:** Store in a cool, well-ventilated area, away from incompatible materials. NFPA 30 Class IB Liquid.

## 8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
Heptane	400 ppm TWA, 500 ppm STEL ACGIH TLV 400 ppm TWA, 500 ppm STEL Canada-Ontario (all isomers) 400 ppm TWA, 500 ppm STEL Canada-Québec 400 ppm TWA, 500 ppm STEL British Columbia
Petroleum Base Oil	5 mg/m <sup>3</sup> TWA (Inhalable) ACGIH TLV (as Mineral oil) 5 mg/m <sup>3</sup> TWA, 10 mg/m <sup>3</sup> STEL Canada- Québec (as oil mist, mineral) 5 mg/m <sup>3</sup> TWA, 10 mg/m <sup>3</sup> STEL Canada- Ontario (as oil mist, mineral) 1 mg/m <sup>3</sup> TWA British Columbia (as Oil mist-mineral, severely refined)
Non-Hazardous Ingredients	None Established
Cyclohexane	100 ppm TWA ACGIH TLV 100 ppm TWA Canada- Ontario 300 ppm TWA Canada- Québec 100 ppm TWA British Columbia

### The Following Controls are Recommended for Normal Consumer Use of this Product

**Appropriate Engineering Controls:** Use in a well-ventilated area.

**Personal Protection:**

**Eye Protection:** Avoid eye contact. Safety glasses or goggles recommended.

**Skin Protection:** Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

**Respiratory Protection:** None needed for normal use with adequate ventilation.

### For Bulk Processing or Workplace Use the Following Controls are Recommended

**Appropriate Engineering Controls:** Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

**Personal Protection:**

**Eye Protection:** Safety goggles recommended where eye contact is possible.

**Skin Protection:** Wear chemical resistant gloves.

**Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

**Work/Hygiene Practices:** Wash with soap and water after handling.

## 9 – Physical and Chemical Properties

Appearance:	Light amber liquid	Flammable Limits:	LEL: 1.0% UEL: 7.0%
Odor:	Mild odor	Vapor Pressure:	45 mmHg @ 20°C
Odor Threshold:	Not established	Vapor Density:	3
pH:	Not Applicable	Relative Density:	0.78 – 0.8
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	199-210°F (93 - 99°C)	Partition Coefficient; n-octanol/water:	Not established
Flash Point:	15-19°F (-9 - -7°C) ASTM D-93	Autoignition Temperature:	Not established
Evaporation Rate:	Not established	Decomposition Temperature:	Not established

Flammability (solid, gas):	Not Applicable	Viscosity:	4.5 cSt (96 SUS) @ 40°C/100°F
VOC:	~40%	Pour Point:	Not established

### 10 – Stability and Reactivity

**Reactivity:** Not reactive under normal conditions

**Chemical Stability:** Stable

**Possibility of Hazardous Reactions:** May react with strong oxidizers generating heat.

**Conditions to Avoid:** Avoid heat, sparks, flames and other sources of ignition.

**Incompatible Materials:** Strong oxidizers, acids and bases.

**Hazardous Decomposition Products:** Carbon monoxide and carbon dioxide.

### 11 – Toxicological Information

**Symptoms of Overexposure:**

**Inhalation:** High concentrations may cause throat, nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Skin Contact:** May cause moderate skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and possible dermatitis.

**Eye Contact:** Contact may cause eye irritation. May cause redness, stinging, swelling and tearing.

**Ingestion:** This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

**Chronic Effects:** Prolonged or repeated skin contact may defeat the skin resulting in irritation and dermatitis.

**Carcinogen Status:** None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

**Reproductive Toxicity:** None of the components is considered a reproductive hazard.

**Numerical Measures of Toxicity:**

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

### 12 – Ecological Information

**Ecotoxicity:** Heptane: 24 hr LC50 Goldfish – 4 mg/L; 24 hr EC50 Daphnia magna – >10 mg/L  
Cyclohexane: 96 hr Pimephales promelas LC50 – 4.53 mg/L; 24 hr EC50 Daphnia magna – >0.9 mg/L

**Persistence and Degradability:** No data available.

**Bioaccumulative Potential:** No data available.

**Mobility in Soil:** No data available

**Other Adverse Effects:** None known

### 13 - Disposal Considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Do not puncture or incinerate containers, even empty. Dispose in accordance with federal, state, and local regulations.

### 14 – Transportation Information

DOT Surface Shipping Description: UN1206, Heptanes, 3, II Ltd. Qty

(Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

Canadian TDG Classification: Limited Quantity

IMDG Shipping Description: UN1206, Heptanes, 3, II LTD QTY

ICAO Shipping Description: UN1206, Heptanes, 3, II

\*Note: Inner packages with less than 5 liters of liquid/ 5 kg of solid are exempt from Marine Pollutant per IMDG Code 2.10.2.7 and ICAO Special Provision A197.

NOTE: WD-40 Company does not test containers to assure that they can withstand the pressure change without leakage when transported by air. We do not recommend that our products be transported by air unless a specific review is conducted.

### 15 – Regulatory Information

**National Pollutant Release Inventory (NPRI):** This product contains the following chemicals that are listed on the NPRI Substance List: Heptane (64742-49-0, 142-82-5) 30-50%, Cyclohexane (110-82-7) <5%

**Canadian Environmental Protection Act:** All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

### 16 – Other Information

**HMIS Hazard Rating:**

**Health – 2 (moderate hazard), Fire Hazard – 3 (serious hazard), Physical Hazard – 0 (minimal hazard)**

Revision Date: March 7, 2016

Supersedes: February 11, 2016

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

Reviewed by: I. Kowalski

Regulatory Affairs Dept.

1062300/No.00127305