

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### WD-40® Specialist® Lawn and Garden Water Protective Silicone

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Lubricant

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited, PO Box 440, Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom  
 Phone:+44 (0) 1908 555400, Fax:+44 (0) 1908 266900  
 www.wd40.co.uk

IRL

P.R. Rielly Limited KarKraft House, Kilbarrack Industrial Estate, Kilbarrack, Dublin 5, Ireland  
 Phone:01-832 0006, Fax:01-832 0016  
 web@team.ie

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:  
 +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)  
 +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (WDC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement                                   |
|--------------|-----------------|--|
| STOT SE      | 3               | H336-May cause drowsiness or dizziness.            |
| Aerosol      | 1               | H222-Extremely flammable aerosol.                  |
| Asp. Tox.    | 1               | H304-May be fatal if swallowed and enters airways. |
| Aerosol      | 1               | H229-Pressurised container: May burst if heated.   |

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 07.03.2017

PDF print date: 09.03.2017

WD-40® Specialist® Lawn and Garden Water Protective Silicone

## Danger

H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.  
 P312-Call a POISON CENTRE / doctor if you feel unwell.  
 P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
 P501-Dispose of contents / container to special waste collection point.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Distillates (petroleum), hydrotreated light

White mineral oil (Natural oil)

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substance

n.a.

### 3.2 Mixture

|  |  |
|--|--|
| <b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b> |  |
| <b>Registration number (REACH)</b>   | 01-2119463258-33-XXXX                                      |
| <b>Index</b>   | ---  |
| <b>EINECS, ELINCS, NLP</b>   | 919-857-5 (REACH-IT List-No.)                              |
| <b>CAS</b>   | ---  |
| <b>content %</b>   | 40-60  |
| <b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>             | Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336 |

|  |                   |
|--|-------------------|
| <b>Petroleum gases, liquified</b>                                  |                   |
| <b>Registration number (REACH)</b>                                 | ---               |
| <b>Index</b>   | 649-202-00-6      |
| <b>EINECS, ELINCS, NLP</b>   | 270-704-2         |
| <b>CAS</b>   | 68476-85-7        |
| <b>content %</b>   | 30-50             |
| <b>Classification according to Regulation (EC) 1272/2008 (CLP)</b> | Flam. Gas 1, H220 |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 07.03.2017

PDF print date: 09.03.2017

WD-40® Specialist® Lawn and Garden Water Protective Silicone

## 4.1 Description of first aid measures

### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

## 4.2 Most important symptoms and effects, both acute and delayed

Irritation of the eyes

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Unconsciousness

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Danger of aspiration

Oedema of the lungs

chemical pneumonitis (condition similar to pneumonia)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

## 4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

Pulmonary oedema prophylaxis

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>

Extinguishment powder

Water jet spray

Alcohol resistant foam

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Formaldehyde

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air mixture

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Page 4 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 07.03.2017 / 0005  
Replacing version dated / version: 30.05.2016 / 0004  
Valid from: 07.03.2017  
PDF print date: 09.03.2017  
WD-40® Specialist® Lawn and Garden Water Protective Silicone

Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Observe special regulations for aerosols!

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
800 mg/m<sup>3</sup>

| (GB) Chemical Name  |  | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | Content %:40-60 |
|---|--|--|-----------------|
| WEL-TWA: 800 mg/m3  |  | WEL-STEL: ---  | ---             |
| Monitoring procedures: <ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul> |  |  |                 |
| BMGV: ---   |  | Other information: (WEL acc. to RCP-method, EH40)                    |                 |

| (IRL) Chemical Name   |  | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | Content %:40-60 |
|---|--|--|-----------------|
| OELV-8h: 100 ppm (573 mg/m3) (White Spirit )  |  | OELV-15min: 125 ppm (720 mg/m3) (White Spirit )                      | ---             |
| Monitoring procedures: <ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul> |  |  |                 |
| BLV: ---  |  | Other information: ---   |                 |

| (GB) Chemical Name   |  | Petroleum gases, liquified                                      | Content %:30-50 |
|--|--|---|-----------------|
| WEL-TWA: 1000 ppm (1750 mg/m3) (Liquefied petroleum gas (LPG)) |  | WEL-STEL: 1250 ppm (2180 mg/m3) (Liquefied petroleum gas (LPG)) | ---             |
| Monitoring procedures: ---                                     |  |   |                 |
| BMGV: ---  |  | Other information: ---  |                 |

| (IRL) Chemical Name            |  | Petroleum gases, liquified        | Content %:30-50 |
|--------------------------------|--|-----------------------------------|-----------------|
| OELV-8h: 1000 ppm (1800 mg/m3) |  | OELV-15min: 1250 ppm (2250 mg/m3) | ---             |
| Monitoring procedures: ---     |  |                                   |                 |
| BLV: ---                       |  | Other information: ---            |                 |

| (GB) Chemical Name  |  | Distillates (petroleum), hydrotreated light | Content %:0,1-<10 |
|---|--|---|-------------------|
| WEL-TWA: 1200 mg/m3 (>= C7 normal and branched chain alkanes)   |  | WEL-STEL: ---                               | ---               |
| Monitoring procedures: <ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul> |  |   |                   |
| BMGV: ---   |  | Other information: ---                      |                   |

| (IRL) Chemical Name   |  | Distillates (petroleum), hydrotreated light | Content %:0,1-<10 |
|---|--|---|-------------------|
| OELV-8h: 600 mg/m3 (AGW)  |  | OELV-15min: 2(II) (AGW)                     | ---               |
| Monitoring procedures: <ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul> |  |   |                   |
| BLV: ---  |  | Other information: ---                      |                   |

| (GB) Chemical Name  |  | Oil mist, mineral          | Content %: |
|---|--|----------------------------|------------|
| WEL-TWA: 5 mg/m3 (ACGIH)  |  | WEL-STEL: 10 mg/m3 (ACGIH) | ---        |
| Monitoring procedures: <ul style="list-style-type: none"> <li>- Draeger - Oil 10/a-P (67 28 371)</li> <li>- Draeger - Oil Mist 1/a (67 33 031)</li> </ul> |  |                            |            |
| BMGV: ---   |  | Other information: ---     |            |

| (IRL) Chemical Name   |  | Oil mist, mineral      | Content %: |
|---|--|------------------------|------------|
| OELV-8h: 5 mg/m3 (Mineral oil, pure, highly & severely refined (inhalable))   |  | OELV-15min: ---        | ---        |
| Monitoring procedures: <ul style="list-style-type: none"> <li>- Draeger - Oil 10/a-P (67 28 371)</li> <li>- Draeger - Oil Mist 1/a (67 33 031)</li> </ul> |  |                        |            |
| BLV: ---  |  | Other information: --- |            |

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(IRL) OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable

Fraction. (R) = Respirable Fraction. | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics |  |                             |            |       |              |      |
|--|--|-----------------------------|------------|-------|--------------|------|
| Area of application  | Exposure route / Environmental compartment | Effect on health            | Descriptor | Value | Unit         | Note |
| Consumer   | Human - oral                               | Long term, systemic effects | DNEL       | 300   | mg/kg bw/day |      |
| Consumer   | Human - dermal                             | Long term, systemic effects | DNEL       | 300   | mg/kg bw/day |      |
| Consumer   | Human - inhalation                         | Long term, systemic effects | DNEL       | 900   | mg/m3        |      |
| Workers / employees  | Human - dermal                             | Long term, systemic effects | DNEL       | 300   | mg/kg bw/day |      |
| Workers / employees  | Human - inhalation                         | Long term, systemic effects | DNEL       | 1500  | mg/m3        |      |

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 With danger of contact with eyes.  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Normally not necessary.  
 with long-term contact:  
 If applicable  
 Protective nitrile gloves (EN 374)  
 Minimum layer thickness in mm:  
 0,4  
 Permeation time (penetration time) in minutes:  
 >= 480  
 Protective Viton® / fluoroelastomer gloves (EN 374)  
 Minimum layer thickness in mm:  
 0,4  
 Permeation time (penetration time) in minutes:  
 >= 480  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.  
 If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |   |
|--|---|
| Physical state:                          | Aerosol. Active substance: liquid.  |
| Colour:                                  | Yellow, Brown   |
| Odour:                                   | Characteristic  |
| Odour threshold:                         | Not determined  |
| pH-value:                                | n.a.  |
| Melting point/freezing point:            | Not determined  |
| Initial boiling point and boiling range: | n.a.  |
| Flash point:                             | n.a.  |
| Evaporation rate:                        | Not determined  |
| Flammability (solid, gas):               | Not determined  |
| Lower explosive limit:                   | 0,8 Vol-%   |
| Upper explosive limit:                   | 9 Vol-%   |
| Vapour pressure:                         | Not determined  |
| Vapour density (air = 1):                | Not determined  |
| Density:                                 | 0,662 g/ml  |
| Bulk density:                            | n.a.  |
| Solubility(ies):                         | Not determined  |
| Water solubility:                        | Insoluble   |
| Partition coefficient (n-octanol/water): | Not determined  |
| Auto-ignition temperature:               | Not determined  |
| Decomposition temperature:               | Not determined  |
| Viscosity:                               | Not determined  |
| Explosive properties:                    | Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture. |
| Oxidising properties:                    | No  |

### 9.2 Other information

|                           |                |
|---------------------------|----------------|
| Miscibility:              | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity:             | Not determined |
| Surface tension:          | Not determined |
| Solvents content:         | Not determined |

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

| WD-40® Specialist® Lawn and Garden Water Protective Silicone  |          |       |      |          |             |        |
|---|----------|-------|------|----------|-------------|--------|
| Toxicity / effect   | Endpoint | Value | Unit | Organism | Test method | Notes  |
| Acute toxicity, by oral route:                                |          |       |      |          |             | n.d.a. |
| Acute toxicity, by dermal route:                              |          |       |      |          |             | n.d.a. |
| Acute toxicity, by inhalation:                                |          |       |      |          |             | n.d.a. |
| Skin corrosion/irritation:                                    |          |       |      |          |             | n.d.a. |
| Serious eye damage/irritation:                                |          |       |      |          |             | n.d.a. |
| Respiratory or skin sensitisation:                            |          |       |      |          |             | n.d.a. |
| Germ cell mutagenicity:                                       |          |       |      |          |             | n.d.a. |
| Carcinogenicity:  |          |       |      |          |             | n.d.a. |
| Reproductive toxicity:  |          |       |      |          |             | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE):   |          |       |      |          |             | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): |          |       |      |          |             | n.d.a. |
| Aspiration hazard:  |          |       |      |          |             | n.d.a. |
| Symptoms:   |          |       |      |          |             | n.d.a. |

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics |          |       |                        |            |  |   |
|--|----------|-------|------------------------|------------|--|---|
| Toxicity / effect  | Endpoint | Value | Unit                   | Organism   | Test method  | Notes   |
| Acute toxicity, by oral route:                                       | LD50     | >5000 | mg/kg                  | Rat        | OECD 401 (Acute Oral Toxicity)                               |   |
| Acute toxicity, by dermal route:                                     | LD50     | >5000 | mg/kg                  | Rabbit     | OECD 402 (Acute Dermal Toxicity)                             |   |
| Acute toxicity, by inhalation:                                       | LC50     | >5000 | mg/m <sup>3</sup> /8 h | Rat        | OECD 403 (Acute Inhalation Toxicity)                         |   |
| Skin corrosion/irritation:   |          |       |                        | Rabbit     | OECD 404 (Acute Dermal Irritation/Corrosion)                 | Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation:                                       |          |       |                        | Rabbit     | OECD 405 (Acute Eye Irritation/Corrosion)                    | Not irritant  |
| Respiratory or skin sensitisation:                                   |          |       |                        | Guinea pig | OECD 406 (Skin Sensitisation)                                | No (skin contact)   |
| Germ cell mutagenicity:  |          |       |                        |            | OECD 471 (Bacterial Reverse Mutation Test)                   | Negative, Analogous conclusion                                      |
| Carcinogenicity:   |          |       |                        |            | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative, Analogous conclusion                                      |
| Reproductive toxicity:   |          |       |                        |            | OECD 414 (Prenatal Developmental Toxicity Study)             | Negative, Analogous conclusion                                      |
| Specific target organ toxicity - single exposure (STOT-SE):          |          |       |                        |            |  | May cause drowsiness or dizziness.                                  |
| Aspiration hazard:   |          |       |                        |            |  | Yes   |



|   |  |  |  |  |  |   |
|---|--|--|--|--|--|---|
| Symptoms:   |  |  |  |  |  | unconsciousness, headaches, dizziness, reddening of the skin                          |
| Symptoms:   |  |  |  |  |  | unconsciousness, headaches, dizziness, discoloration of the skin, vomiting, diarrhoea |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: |  |  |  |  | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Not to be expected  |

| Petroleum gases, liquified     |          |       |      |          |             |              |
|--------------------------------|----------|-------|------|----------|-------------|--------------|
| Toxicity / effect              | Endpoint | Value | Unit | Organism | Test method | Notes        |
| Acute toxicity, by inhalation: | LC50     | >5    | mg/l |          |             |              |
| Skin corrosion/irritation:     |          |       |      |          |             | Not irritant |
| Serious eye damage/irritation: |          |       |      |          |             | Not irritant |

| Distillates (petroleum), hydrotreated light |          |       |      |          |             |       |
|---|----------|-------|------|----------|-------------|-------|
| Toxicity / effect                           | Endpoint | Value | Unit | Organism | Test method | Notes |
| Aspiration hazard:                          |          |       |      |          |             | Yes   |

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| WD-40® Specialist® Lawn and Garden Water Protective Silicone |          |      |       |      |          |             |  |
|--|----------|------|-------|------|----------|-------------|--|
| Toxicity / effect  | Endpoint | Time | Value | Unit | Organism | Test method | Notes  |
| 12.1. Toxicity to fish:                                      |          |      |       |      |          |             | n.d.a.   |
| 12.1. Toxicity to daphnia:                                   |          |      |       |      |          |             | n.d.a.   |
| 12.1. Toxicity to algae:                                     |          |      |       |      |          |             | n.d.a.   |
| 12.2. Persistence and degradability:                         |          |      |       |      |          |             | Isolate as much as possible with an oil separator. |
| 12.3. Bioaccumulative potential:                             |          |      |       |      |          |             | n.d.a.   |
| 12.4. Mobility in soil:                                      |          |      |       |      |          |             | n.d.a.   |
| 12.5. Results of PBT and vPvB assessment                     |          |      |       |      |          |             | n.d.a.   |
| 12.6. Other adverse effects:                                 |          |      |       |      |          |             | n.d.a.   |
| Other information:   |          |      |       |      |          |             | According to the recipe, contains no AOX.          |

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics |          |      |       |      |                     |  |       |
|--|----------|------|-------|------|---------------------|--|-------|
| Toxicity / effect  | Endpoint | Time | Value | Unit | Organism            | Test method                                      | Notes |
| 12.1. Toxicity to fish:  | LC50     | 96h  | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test)             |       |
| 12.1. Toxicity to fish:  | NOELR    | 28d  | 0,13  | mg/l | Oncorhynchus mykiss | QSAR   |       |
| 12.1. Toxicity to daphnia:   | EC50     | 48h  | >1000 | mg/l | Daphnia magna       | OECD 202 (Daphnia sp. Acute Immobilisation Test) |       |

|  |       |     |       |      |                                  |  |                                     |
|--|-------|-----|-------|------|----------------------------------|--|-------------------------------------|
| 12.1. Toxicity to daphnia:               | NOELR | 21d | 0,23  | mg/l | Daphnia magna                    | QSAR   |                                     |
| 12.1. Toxicity to algae:                 | NOELR | 72h | 100   | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| 12.1. Toxicity to algae:                 | ErC50 | 72h | >1000 | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| 12.1. Toxicity to algae:                 | EbC50 | 72h | >1000 | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| 12.1. Toxicity to algae:                 | ErC50 | 72h | >1000 | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| 12.1. Toxicity to algae:                 | EbC50 | 72h | >1000 | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| 12.1. Toxicity to algae:                 | NOELR | 72h | 100   | mg/l | Raphidocelis subcapitata         | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| 12.2. Persistence and degradability:     |       | 28d | 80    | %    |                                  | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable               |
| 12.5. Results of PBT and vPvB assessment |       |     |       |      |                                  |  | No PBT substance, No vPvB substance |

**Petroleum gases, liquified**

| Toxicity / effect                | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|----------------------------------|----------|------|-------|------|----------|-------------|-------|
| 12.3. Bioaccumulative potential: |          |      |       |      |          |             | No    |

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****For the substance / mixture / residual amounts**

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 04 other organic solvents, washing liquids and mother liquors

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

**For contaminated packing material**

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

**SECTION 14: Transport information****General statements**

14.1. UN number:

1950

**Transport by road/by rail (ADR/RID)**

14.2. UN proper shipping name:

UN 1950 AEROSOLS



|                                   |                |
|-----------------------------------|----------------|
| 14.3. Transport hazard class(es): | 2.1            |
| 14.4. Packing group:              | -              |
| Classification code:              | 5F             |
| LQ:                               | 1 L            |
| 14.5. Environmental hazards:      | Not applicable |
| Tunnel restriction code:          | D              |

**Transport by sea (IMDG-code)**

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

**Transport by air (IATA)**

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

14.5. Environmental hazards: Not applicable

**14.6. Special precautions for user**

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): ~ 92 %

Observe incident regulations.

Observe youth employment law (German regulation).

**15.2 Chemical safety assessment**

A chemical safety assessment is not provided for mixtures.

**SECTION 16: Other information**

EU F0052

Revised sections:

2, 3, 8, 11, 12, 13

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Employee training in handling dangerous goods is required.

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used                              |
|---|---|
| STOT SE 3, H336   | Classification according to calculation procedure.  |
| Aerosol 1, H222   | Classification according to calculation procedure.  |
| Asp. Tox. 1, H304   | Classification according to calculation procedure.  |
| Aerosol 1, H229   | Classification based on the form or physical state. |

Page 12 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0005  
 Replacing version dated / version: 30.05.2016 / 0004  
 Valid from: 07.03.2017  
 PDF print date: 09.03.2017  
 WD-40® Specialist® Lawn and Garden Water Protective Silicone

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H336 May cause drowsiness or dizziness.  
 H220 Extremely flammable gas.

STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Aerosol — Aerosols  
 Asp. Tox. — Aspiration hazard  
 Flam. Liq. — Flammable liquid  
 Flam. Gas — Flammable gases (including chemically unstable gases)

### Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to  
 ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand  
 CTFA Cosmetic, Toiletry, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue  
 Fax. Fax number  
 gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
HGWP Halocarbon Global Warming Potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC Intermediate Bulk Container  
IBC (Code) International Bulk Chemical (Code)  
IC Inhibitory concentration  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LC lethal concentration  
LC50 lethal concentration 50 percent kill  
LCLo lowest published lethal concentration  
LD Lethal Dose of a chemical  
LD50 Lethal Dose, 50% kill  
LDLo Lethal Dose Low  
LOAEL Lowest Observed Adverse Effect Level  
LOEC Lowest Observed Effect Concentration  
LOEL Lowest Observed Effect Level  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization

Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 07.03.2017

PDF print date: 09.03.2017

WD-40® Specialist® Lawn and Garden Water Protective Silicone

---

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.