Product name: WD-40® Specialist® High Performance White Page: 1/10

Lithium Grease

Supersedes date: Revision: 2019-03-13

Product No.: SDS-ID: IL-EN/1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: WD-40® Specialist® High Performance White Lithium Grease

Container size: 400 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

<u>Application:</u> Universal lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier: WD-40

Brick Close | Kiln Farm MK11 3LJ Milton Keynes

United Kingdom

Supplier: Hashahal, Inc.

HaRav Shalom Jarufi St 4

Rishon LeTsiyon Tel:03-7612700

1.4. Emergency telephone number

Emergency telephone: Israel Poison Information Center: 04-7771900 (24/7)

Product name: WD-40® Specialist® High Performance White Page: 2/10

Lithium Grease

Supersedes date: Revision: 2019-03-13

Product No.: SDS-ID: IL-EN/1.0

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The product is classified:

GHS: Flam. Aerosol 1 - Skin Irrit. 2 - STOT SE 3;H336 - Asp. Tox. 1 - Aquatic Chronic 2

2.2. Label elements



Danger

Contains: Naphtha (petroleum), hydrotreated light

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

P211 Do not spray on an open flame or other ignition source.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

2.3. Other hazards

PBT/vPvB: This product does not contain any PBT or vPvB substances.

Other: Aerosol containers can burst violently when heated, due to excess pressure

build-up. The product contains volatile, organic compounds which have a photochemical ozone creation potential. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system,

including the brain.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains: organic solvents, propellants and mineral oil.

Product name: WD-40® Specialist® High Performance White Page: 3/10

Lithium Grease

Supersedes date: Revision: 2019-03-13

Product No.: SDS-ID: IL-EN/1.0

GHS:

 %:
 CAS-No.:
 EC No.:
 Chemical name:
 Hazard classification:
 Notes:

 > 60
 68476-85-7
 270-704-2
 Liquefied petroleum gas
 Flam. Gas 1;H220
 K

Press. Gas, Compressed;H280

10-30 - Naphtha (petroleum), hydrotreated Flam. Liq. 2;H225 **

Skin Irrit. 2;H315 STOT SE 3;H336 Asp. Tox. 1;H304

Aquatic Chronic 2;H411

1-5 1174522-15-6 926-141-6 Hydrocarbons, C11-C14, n-alkanes, Flam. Liq. 3;H226

isoalkanes, cyclics, <2% aromatics Asp. Tox. 1;H304

Notes: K: 1,3-butadien < 0.1% (w/w)

**Contains one or more of the following EINECS-numbers: 931-254-9, 265-151-9,

927-510-4.

light

Reference: The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Inhalation: Move injured person into fresh air and keep person calm under observation. If

uncomfortable: Seek hospital and bring along these instructions.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water. In case of

eczema or other skin disorders: Seek medical attention and bring these

instructions.

<u>Eye contact:</u> Immediately flush with plenty of water for at least 15 minutes. Remove any

contact lenses and open eyelids widely. If irritation persists: Seek medical

attention and bring along these instructions.

Ingestion: Aspiration hazard. Immediately rinse mouth and drink plenty of water or milk.

Keep person under observation. Do not induce vomiting. If vomiting occurs, keep

head low. Immediate transport to hospital. Bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: Be aware that symptoms of lung oedema (shortness of breath) may develop up

to 24 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically. If there is any suspicion of aspiration into the lungs either

directly or as a result of vomiting, obtain medical advice.

Product name: WD-40® Specialist® High Performance White Page: 4/10

Lithium Grease

Supersedes date: Revision: 2019-03-13

Product No.: SDS-ID: IL-EN/1.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Extinguish with carbon dioxide or dry powder. Cool containers exposed to heat

with water spray and remove container, if no risk is involved.

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards: Aerosol containers can explode when heated, due to excessive pressure build-

up. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

<u>Protective equipment for fire-</u> Selection of respiratory protection for fire fighting: follow the general fire

<u>fighters:</u> precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Follow precautions for safe handling described in this safety data sheet. Avoid

inhalation of vapours and aerosols and contact with skin and eyes. Do not smoke

or use open fire, or other sources of ignition.

6.2. Environmental precautions

<u>Environmental</u> Avoid discharge into drains, water courses or onto the ground.

precautions:

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Absorb spillage with non-combustible, absorbing material. Clean contaminated

area with oil-removing material.

6.4. Reference to other sections

Reference: For personal protection, see section 8. For waste disposal, see section 13.

Product name: WD-40® Specialist® High Performance White Page: 5/10

Lithium Grease

Supersedes date: Revision: 2019-03-13

Product No.: SDS-ID: IL-EN/1.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

<u>Safe handling advice:</u> Observe good chemical hygiene practices.

Work practice should minimise contact. Avoid inhalation of vapours and spray

mists. Avoid contact with skin and eyes.

<u>Technical measures:</u> Do not smoke or use open fire or other sources of ignition. Work practice should

minimise contact. Do not eat, drink or smoke when using the product.

<u>Technical precautions:</u> Provide adequate ventilation. Provide easy access to water supply or an

emergency shower. First-aid equipment, including eye wash bottle, must be available at the work site. Provide access to washing facilities incl. soap, skin

cleanser, barrier cream and fatty cream.

7.2. Conditions for safe storage, including any incompatibilities

<u>Technical measures for safe</u> Follow the rules for storage of flammable products.

storage:

Store in a cool and well-ventilated place. Do not store near heat sources or

expose to high temperatures.

Specific use(s): Not relevant.

Product name: WD-40® Specialist® High Performance White Page: 6/10

Lithium Grease

Supersedes date: Revision: 2019-03-13

Product No.: SDS-ID: IL-EN/1.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

CAS-No.: Chemical name: As: Exposure limits: Type: Notes: References:

68476-85-7 Liquefied petroleum gas - Simple ACGIH

asphyxiant

(D); EX

EX: Explosion hazard.

·

8.2. Exposure controls

Notes:

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and

minimize the risk of inhalation of vapours and aerosols.

<u>Personal protection:</u> Personal protection equipment should be chosen according to the ANSI

standards and in discussion with the supplier of the personal protective

equipment.

Respiratory equipment: In case of inadequate ventilation and work of brief duration, use suitable

respiratory equipment. In case of inadequate ventilation: It is recommended to

use respiratory equipment with combination filter, type A2/P2.

Hand protection: Risk of contact: Wear protective gloves. It is recommended to use gloves of

Viton or nitrile rubber. Thickness: ≥ 0,4 mm. Breakthrough time: 480 min. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Other types of gloves can be recommended by the glove supplier.

Eye protection: Risk of contact: Wear goggles/face shield.

Hygiene measures: Wash hands after handling. Do not eat, drink or smoke when using the

product. Change contaminated clothing. Wash contaminated clothing before

reuse.

Environmental Exposure

Controls:

Not available.

WD-40® Specialist® High Performance White 7/10 Product name: Page:

Lithium Grease

Supersedes date: Revision: 2019-03-13

SDS-ID: Product No.: IL-EN/1.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Aerosol. Appearance: Colour: White.

Odour: Characteristic. pH: Not available. Melting point / freezing point: Not available. Not available. **Boiling point:** Flash point: Not available. **Explosion limits:** Not available. Not available. Vapour pressure:

Solubility: Insoluble in water.

Partition coefficient

Not available.

(n-octanol/water):

Vapour density:

Relative density:

Decomposition Not available.

temperature (°C):

< 7 mm²/s (liquid phase) Viscosity:

9.2. Other information

Other data: Not available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Not reactive.

10.2. Chemical stability

Stability: Stable under normal temperature conditions.

Not available.

Not available.

10.3. Possibility of hazardous reactions

None known. Hazardous reactions:

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and other sources of ignition. Avoid exposure to high

temperatures or direct sunlight.

10.5. Incompatible materials

Incompatible materials: Strong oxides.

10.6. Hazardous decomposition products

Hazardous decomposition

None in particular.

products:

Product name: WD-40® Specialist® High Performance White 8/10 Page:

Lithium Grease

Supersedes date: 2019-03-13 Revision:

Product No.: SDS-ID: IL-EN/1.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute Toxicity (Oral): Based on available data, the classification criteria are not met. Acute Toxicity (Dermal): Based on available data, the classification criteria are not met. Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin

sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Reproductive Toxicity:

STOT - Single exposure: May cause drowsiness or dizziness.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

May be fatal if swallowed and enters airways. Aspiration hazard:

Inhalation: In high concentrations, vapours and spray mists are narcotic and may cause

headache, fatigue, dizziness and nausea.

Irritating and degreasing. Skin contact:

Irritating and may cause redness and pain. Eye contact:

Ingestion: Low order of acute toxicity, but aspiration following ingestion and vomiting may

cause severe and potentially fatal chemical pneumonitis.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Degradability: The degradability of the product has not been stated.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

No data available. Mobility:

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances. PBT/vPvB:

12.6. Other adverse effects

Other adverse effects: The product contains volatile, organic compounds which have a photochemical

ozone creation potential.

An oil film may cause physical damage to organisms and disturb the

transportation of oxygen in the intermediate zone between air/water or water/air.

Product name: WD-40® Specialist® High Performance White Page: 9/10

Lithium Grease

Supersedes date: Revision: 2019-03-13
Product No.: SDS-ID: IL-EN/1.0

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Do not puncture or incinerate even when empty.

Contaminated packaging: Empty aerosol containers before disposal.

SECTION 14: TRANSPORT INFORMATION

The product is covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

<u>UN-No:</u> 1950

14.2. UN proper shipping name

Proper Shipping Name: AEROSOLS, flammable

14.3. Transport hazard class(es)

Class: 2

14.4. Packing group

<u>PG:</u> -

14.5. Environmental hazards

Marine pollutant: Yes.

Environmentally Hazardous Yes.

Substance:

14.6. Special precautions for user

<u>Special precautions:</u> None known.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

<u>Transport in bulk:</u> This product is not intended for transport in bulk.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: Work Safety Regulations (Safety Data Sheets, Classification, Packing, Labeling

and Marking of Packages), 5758-1998, with amendments.

Threshold Limit Values (2018), ACGIH, by the American Conference on

Governmental Industrial Hygienists.

Product name: WD-40® Specialist® High Performance White Page: 10/10

Lithium Grease

Supersedes date: Revision: 2019-03-13

Product No.: SDS-ID: IL-EN/1.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

<u>Abbreviations and acronyms</u> PBT = Persistent, Bioaccumulative and Toxic. <u>used in the safety data sheet:</u> vPvB = very Persistent and very Bioaccumulative.

<u>Additional information:</u> Classification according to Regulation (EC) No. 1272/2008:

Health Hazards: Calculation method. Physical Hazards: Expert judgement.

Wording of H-statements:

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.