

SAFETY DATA SHEET

Product name: WD-40® Specialist® Silicone Lubricant Page: 1/11
Supersedes date: Revision: 2018-12-11
Product No.: SDS-ID: IL-EN/1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: WD-40® Specialist® Silicone Lubricant
Container size: 200 ml, 400 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Universal lubricant.

1.3. Details of the supplier of the safety data sheet

Manufacturer: WD-40
Brick Close | Kiln Farm
MK11 3LJ Milton Keynes
United Kingdom

Supplier: Hashahal, Inc.
HaRav Shalom Jarufi St 4
Rishon LeTsiyon
Tel:03-7612700

1.4. Emergency telephone number

Emergency telephone: Israel Poison Information Center: 04-7771900 (24/7)

SAFETY DATA SHEET

Product name: WD-40® Specialist® Silicone Lubricant Page: 2/11
Supersedes date: Revision: 2018-12-11
Product No.: SDS-ID: IL-EN/1.0

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The product is classified:

GHS: Flam. Aerosol 1 - STOT SE 3;H336 - Asp. Tox. 1

2.2. Label elements



Danger

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

H222 Extremely flammable aerosol.

H336 May cause drowsiness or dizziness.

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

P211 Do not spray on an open flame or other ignition source.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

PBT/vPvB: This product does not contain any PBT or vPvB substances.

Other: Aerosol containers can burst violently when heated, due to excess pressure build-up. The product contains volatile, organic compounds which have a photochemical ozone creation potential. The product contains organic solvents. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains: organic solvents, propellants and mineral oil.

SAFETY DATA SHEET

Product name: WD-40® Specialist® Silicone Lubricant Page: 3/11
Supersedes date: Revision: 2018-12-11
Product No.: SDS-ID: IL-EN/1.0

GHS:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
30-60	-	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Flam. Liq. 3;H226 STOT SE 3;H336 Asp. Tox. 1;H304	
1-5	8042-47-5	232-455-8	White mineral oil (petroleum)	Asp. Tox. 1;H304	
1-5	64742-47-8	265-149-8	Distillates (petroleum), hydrotreated light	Flam. Liq. 3;H226 Asp. Tox. 1;H304	

Reference: The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Inhalation: Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring along these instructions.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water. In case of eczema or other skin disorders: Seek medical attention and bring these instructions.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: Aspiration hazard. Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Immediate transport to hospital. Bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically. If there is any suspicion of aspiration into the lungs either directly or as a result of vomiting, obtain medical advice.

SAFETY DATA SHEET

Product name:	WD-40® Specialist® Silicone Lubricant	Page:	4/11
Supersedes date:		Revision:	2018-12-11
Product No.:		SDS-ID:	IL-EN/1.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Extinguish with carbon dioxide or dry powder. Cool containers exposed to heat with water spray and remove container, if no risk is involved.
Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards: Aerosol containers can explode when heated, due to excessive pressure build-up. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire-fighters: Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Do not smoke or use open fire, or other sources of ignition.

6.2. Environmental precautions

Environmental precautions: Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Absorb spillage with non-combustible, absorbing material. Clean contaminated area with oil-removing material.

6.4. Reference to other sections

Reference: For personal protection, see section 8. For waste disposal, see section 13.

SAFETY DATA SHEET

Product name:	WD-40® Specialist® Silicone Lubricant	Page:	5/11
Supersedes date:		Revision:	2018-12-11
Product No.:		SDS-ID:	IL-EN/1.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Observe good chemical hygiene practices. Work practice should minimise contact. Avoid inhalation of vapours and spray mists. Avoid contact with skin and eyes.

Technical measures: Do not smoke or use open fire or other sources of ignition. Work practice should minimise contact. Do not eat, drink or smoke when using the product.

Technical precautions: Provide adequate ventilation. Provide easy access to water supply or an emergency shower. First-aid equipment, including eye wash bottle, must be available at the work site. Provide access to washing facilities incl. soap, skin cleanser, barrier cream and fatty cream.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for safe storage: Follow the rules for storage of flammable products.

Storage conditions: Store in a cool and well-ventilated place. Do not store near heat sources or expose to high temperatures.

SAFETY DATA SHEET

Product name: WD-40® Specialist® Silicone Lubricant Page: 6/11
Supersedes date: Revision: 2018-12-11
Product No.: SDS-ID: IL-EN/1.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>	<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
-	Mineral oil, excluding metal working fluids (pure, highly and severely refined), inhalable particulate matter	-	5 mg/m3	TWA	A4	ACGIH

8.2. Exposure controls

<u>Engineering measures:</u>	Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapours and aerosols.
<u>Personal protection:</u>	Personal protection equipment should be chosen according to the ANSI standards and in discussion with the supplier of the personal protective equipment.
<u>Respiratory equipment:</u>	In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. In case of inadequate ventilation: It is recommended to use respiratory equipment with combination filter, type A2/P2.
<u>Hand protection:</u>	Risk of contact: Wear protective gloves. It is recommended to use gloves of Viton or nitrile rubber. Thickness: ≥ 0,4 mm. Breakthrough time: ≥ 480 min. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Other types of gloves can be recommended by the glove supplier.
<u>Eye protection:</u>	Risk of contact: Wear goggles/face shield.
<u>Hygiene measures:</u>	Wash hands after handling. Do not eat, drink or smoke when using the product. Change contaminated clothing. Wash contaminated clothing before reuse.
<u>Environmental Exposure Controls:</u>	Not available.

SAFETY DATA SHEET

Product name:	WD-40® Specialist® Silicone Lubricant	Page:	7/11
Supersedes date:		Revision:	2018-12-11
Product No.:		SDS-ID:	IL-EN/1.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<u>Appearance:</u>	Aerosol.
<u>Colour:</u>	Light brown.
<u>Odour:</u>	Characteristic.
<u>pH:</u>	Not available.
<u>Melting point / freezing point:</u>	Not available.
<u>Boiling point:</u>	Not available.
<u>Flash point:</u>	Not available.
<u>Explosion limits:</u>	0,8 % - 9 %
<u>Vapour pressure:</u>	Not available.
<u>Vapour density:</u>	Not available.
<u>Relative density:</u>	0,662
<u>Solubility:</u>	Insoluble in water.
<u>Partition coefficient (n-octanol/water):</u>	Not available.
<u>Decomposition temperature (°C):</u>	Not available.
<u>Viscosity:</u>	Not available.

9.2. Other information

<u>Other data:</u>	Not available.
--------------------	----------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

<u>Reactivity:</u>	Not reactive.
--------------------	---------------

10.2. Chemical stability

<u>Stability:</u>	Stable under normal temperature conditions.
-------------------	---

10.3. Possibility of hazardous reactions

<u>Hazardous reactions:</u>	None known.
-----------------------------	-------------

10.4. Conditions to avoid

<u>Conditions to avoid:</u>	Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.
-----------------------------	---

10.5. Incompatible materials

<u>Incompatible materials:</u>	Strong oxides.
--------------------------------	----------------

10.6. Hazardous decomposition products

<u>Hazardous decomposition products:</u>	None in particular.
--	---------------------

SAFETY DATA SHEET

Product name:	WD-40® Specialist® Silicone Lubricant	Page:	8/11
Supersedes date:		Revision:	2018-12-11
Product No.:		SDS-ID:	IL-EN/1.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis.

Acute Toxicity (Oral): Based on available data, the classification criteria are not met.

Acute Toxicity (Dermal): Based on available data, the classification criteria are not met.

Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: May cause drowsiness or dizziness.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

Inhalation: In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin contact: Prolonged contact may cause redness, irritation and dry skin.

Eye contact: May irritate and cause redness and pain.

Ingestion: Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis.

SAFETY DATA SHEET

Product name:	WD-40® Specialist® Silicone Lubricant	Page:	9/11
Supersedes date:		Revision:	2018-12-11
Product No.:		SDS-ID:	IL-EN/1.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Degradability: The degradability of the product has not been stated.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Other adverse effects: The product contains volatile, organic compounds which have a photochemical ozone creation potential.
An oil film may cause physical damage to organisms and disturb the transportation of oxygen in the intermediate zone between air/water or water/air.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste. Do not puncture or incinerate even when empty.

Waste from residues: Used cloths, etc. EWC-code: 15 02 02

Contaminated packaging: EWC-code: 15 01 11
Empty aerosol containers before disposal.

SAFETY DATA SHEET

Product name:	WD-40® Specialist® Silicone Lubricant	Page:	10/11
Supersedes date:		Revision:	2018-12-11
Product No.:		SDS-ID:	IL-EN/1.0

SECTION 14: TRANSPORT INFORMATION

The product is covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN-No: 1950

14.2. UN proper shipping name

Proper Shipping Name: AEROSOLS, flammable

14.3. Transport hazard class(es)

Class: 2

14.4. Packing group

PG: -

14.5. Environmental hazards

Marine pollutant: Yes.

Environmentally Hazardous Substance: Yes.

14.6. Special precautions for user

Special precautions: None known.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: This product is not intended for transport in bulk.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: Work Safety Regulations (Safety Data Sheets, Classification, Packing, Labeling and Marking of Packages), 5758-1998, with amendments.

SAFETY DATA SHEET

Product name:	WD-40® Specialist® Silicone Lubricant	Page:	11/11
Supersedes date:		Revision:	2018-12-11
Product No.:		SDS-ID:	IL-EN/1.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Abbreviations and acronyms used in the safety data sheet: PBT = Persistent, Bioaccumulative and Toxic.
vPvB = very Persistent and very Bioaccumulative.

Additional information: Classification according to Regulation (EC) No. 1272/2008:
Health Hazards: Calculation method.
Physical Hazards: Expert judgement.

Wording of H-statements:

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.
www.dhigroup.com.
