

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 1/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### **1.1. Product identifier**

Product name: WD-40® Specialist® High Performance Lubricant with PTFE  
Container size: 250 ml, 400 ml

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Application: Lubricant.

### **1.3. Details of the supplier of the safety data sheet**

Manufacturer: WD-40  
Brick Close | Kiln Farm  
MK11 3LJ Milton Keynes  
United Kingdom

Supplier/Distributor: Hashahal, Inc.  
HaRav Shalom Jarufi St 4  
Rishon LeTsiyon  
Tel:03-7612700

### **1.4. Emergency telephone number**

Emergency telephone: Israel Poison Information Center: 04-7771900 (24/7)

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 2/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

SI 2302 (1): The product is classified: Flam. Aerosol 1 - Skin Irrit. 2 - STOT SE 3;H336 - Asp. Tox. 1 - Aquatic Chronic 2

### 2.2. Label elements



Danger

Contains: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics  
Hydrocarbons, C7-C9, isoalkanes  
Distillates (petroleum), hydrotreated light

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

P211 Do not spray on an open flame or other ignition source.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local regulations.

Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts. May produce an allergic reaction.

### 2.3. Other hazards

PBT/vPvB: This product does not contain any PBT or vPvB substances.

Other: Aerosol containers can burst violently when heated, due to excess pressure build-up. The product contains volatile, organic compounds which have a photochemical ozone creation potential. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 3/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

---

## **3.2. Mixtures**

The product contains: organic solvents, propellants and mineral oil.

SI 2302 (1):

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
25-40	-	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Flam. Liq. 2;H225 Skin Irrit. 2;H315 STOT SE 3;H336 Asp. Tox. 1;H304 Aquatic Chronic 2;H411	
20-30	-	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Flam. Liq. 3;H226 STOT SE 3;H336 Asp. Tox. 1;H304	
10-30	68476-85-7	270-704-2	Petroleum gases, liquefied	Flam. Gas 1;H220 Press. Gas, Compressed;H280	K
1-5	64741-66-8	921-728-3	Hydrocarbons, C7-C9, isoalkanes	Flam. Liq. 2;H225 Skin Irrit. 2;H315 STOT SE 3;H336 Asp. Tox. 1;H304 Aquatic Chronic 2;H411	
1-5	64742-47-8	265-149-8	Distillates (petroleum), hydrotreated light	Flam. Liq. 3;H226 Asp. Tox. 1;H304	
1 - < 10	-	939-603-7	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts	Skin Sens. 1B;H317	

Notes: K: 1,3-butadien < 0.1% (w/w)

Reference: The full text for all hazard statements is displayed in section 16.

---

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 4/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Inhalation: Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring along these instructions.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water. In case of eczema or other skin disorders: Seek medical attention and bring these instructions.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: Not likely, due to the form of the product. In case of ingestion: Aspiration hazard. Immediately rinse mouth and drink 1-2 glasses of water. DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: Dizziness. Headache. Coughing. Eye irritation. Dermatitis possible through repeated contact.  
Ingestion: Aspiration hazard. Nausea, vomiting. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Extinguishing media: Extinguish with carbon dioxide or dry powder. Cool containers exposed to heat with water spray and remove container, if no risk is involved.  
Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards: Aerosol containers can explode when heated, due to excessive pressure build-up. During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

Protective equipment for fire-fighters: Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 5/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Do not smoke or use open fire, or other sources of ignition.

### **6.2. Environmental precautions**

Environmental precautions: Avoid discharge into drains, water courses or onto the ground.

### **6.3. Methods and material for containment and cleaning up**

Methods for cleaning up: Absorb spillage with non-combustible, absorbing material. Clean contaminated area with oil-removing material.

### **6.4. Reference to other sections**

Reference: For personal protection, see section 8. For waste disposal, see section 13.

## SECTION 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

Safe handling advice: Observe good chemical hygiene practices. Work practice should minimise contact. Avoid inhalation of vapours and spray mists. Avoid contact with skin and eyes.

Technical measures: Do not smoke or use open fire or other sources of ignition. Work practice should minimise contact. Do not eat, drink or smoke when using the product.

Technical precautions: Provide adequate ventilation. Provide easy access to water supply or an emergency shower. First-aid equipment, including eye wash bottle, must be available at the work site. Provide access to washing facilities incl. soap, skin cleanser, barrier cream and fatty cream.

### **7.2. Conditions for safe storage, including any incompatibilities**

Technical measures for safe storage: Follow the rules for storage of flammable products.

Storage conditions: Store in a cool and well-ventilated place. Do not store near heat sources or expose to high temperatures. Store at temperature below 50°C. Protect against direct sunlight.

Specific use(s): Not relevant.

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 6/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>	<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
68476-85-7	Liquefied petroleum gas	-			Simple asphyxiant (D); EX	ACGIH
-	Mineral oil, excluding metal working fluids (poorly and mildly refined)	-			A2	ACGIH
-	Mineral oil, excluding metal working fluids (pure, highly and severely refined), inhalable particulate matter	-	5 mg/m3	TWA	A4	ACGIH

Notes:

A2: Suspected Human Carcinogen.  
A4: Not Classifiable as a Human Carcinogen.

### 8.2. Exposure controls

<u>Engineering measures:</u>	Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapours and aerosols.
<u>Personal protection:</u>	Personal protection equipment should be chosen according to the ANSI standards and in discussion with the supplier of the personal protective equipment.
<u>Respiratory equipment:</u>	In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment.
<u>Hand protection:</u>	Risk of contact: Wear protective gloves. It is recommended to use gloves of Viton or nitrile rubber. Thickness: $\geq 0,4$ mm. Breakthrough time: $\geq 480$ min. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Other types of gloves can be recommended by the glove supplier.
<u>Eye protection:</u>	Risk of contact: Wear goggles/face shield.
<u>Hygiene measures:</u>	Wash hands after handling. Do not eat, drink or smoke when using the product. Change contaminated clothing. Wash contaminated clothing before reuse. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Private clothes and working clothes should be kept separately.
<u>Environmental Exposure Controls:</u>	Not available.

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 7/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance: Aerosol.  
Colour: Light brown.  
Odour: Hydrocarbons.  
pH: Not available.  
Melting point / freezing point: Not available.  
Boiling point: Not available.  
Flash point: Not available.  
Explosion limits: 0.8-9%-vol  
Vapour pressure: Not available.  
Vapour density: Not available.  
Relative density: 0,706 g/ml  
Solubility: Insoluble in water.  
Partition coefficient (n-octanol/water): Not available.  
Decomposition temperature (°C): Not available.  
Viscosity: Not available.  
Explosive properties: Non-explosive.

### 9.2. Other information

Other data: Not available.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Reactivity: Not reactive.

### 10.2. Chemical stability

Stability: Stable under the prescribed storage conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: None known.

### 10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

### 10.5. Incompatible materials

Incompatible materials: Strong oxides.

### 10.6. Hazardous decomposition products

Hazardous decomposition products: None in particular.

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 8/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Acute Toxicity (Oral): Based on available data, the classification criteria are not met.

Acute Toxicity (Dermal): Based on available data, the classification criteria are not met.

Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation: Causes skin irritation.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: May cause drowsiness or dizziness.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

Inhalation: In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

Skin contact: Irritating and degreasing. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

Eye contact: May irritate and cause redness and pain.

Ingestion: Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis.



# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 9/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 12: ECOLOGICAL INFORMATION

### **12.1. Toxicity**

Ecotoxicity: Toxic to aquatic life with long lasting effects.

### **12.2. Persistence and degradability**

Degradability: The degradability of the product has not been stated.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential: No data available on bioaccumulation.

### **12.4. Mobility in soil**

Mobility: No data available.

### **12.5. Results of PBT and vPvB assessment**

PBT/vPvB: This product does not contain any PBT or vPvB substances.

### **12.6. Other adverse effects**

Other adverse effects: The product contains volatile, organic compounds which have a photochemical ozone creation potential.  
An oil film may cause physical damage to organisms and disturb the transportation of oxygen in the intermediate zone between air/water or water/air.

## SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements. Do not puncture or incinerate even when empty.

Contaminated packaging: Empty aerosol containers before disposal.

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 10/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 14: TRANSPORT INFORMATION

The product is covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

UN-No: 1950

### 14.2. UN proper shipping name

Proper Shipping Name: AEROSOLS, flammable

### 14.3. Transport hazard class(es)

Class: 2

### 14.4. Packing group

PG: -

### 14.5. Environmental hazards

Marine pollutant: Yes.

Environmentally Hazardous Substance: Yes.

### 14.6. Special precautions for user

Special precautions: None known.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: This product is not intended for transport in bulk.

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: SI 2302 part 1 - Dangerous substances and mixtures: Classification, labelling, marking and packaging, with amendments.  
Work Safety Regulations (Safety Data Sheets, Classification, Packing, Labeling and Marking of Packages), 5758-1998, with amendments.  
Threshold Limit Values (2018), ACGIH, by the American Conference on Governmental Industrial Hygienists.

# SAFETY DATA SHEET

Product name: WD-40® Specialist® High Performance Lubricant with PTFE Page: 11/11  
Supersedes date: Revision: 2020-02-21  
Product No.: SDS-ID: IL-EN/1.0

## SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Abbreviations and acronyms used in the safety data sheet: PBT = Persistent, Bioaccumulative and Toxic.  
vPvB = very Persistent and very Bioaccumulative.

Additional information: Classification according to Regulation (EC) No. 1272/2008:  
Health Hazards: Calculation method.  
Physical Hazards: Expert judgement.

### Wording of H-statements:

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.  
[www.dhigroup.com](http://www.dhigroup.com).